



Verifone P400

Our most advanced PIN pad, designed for performance and security. This premium device encourages greater customer engagement and better returns.

PROCESSOR

600 MHz, 1500 MIPS, Arm Cortex-A9
32-bit RISC

MEMORY

384 MB (256 MB Flash, 128 MB SDRAM),
microSD

DISPLAY

3.5" HVGA color, capacitive touchscreen,
Corning® Gorilla® Glass technology

OPERATING SYSTEM

V/OS (Linux-based)

CONNECTIVITY

Ethernet

CARD READERS

Triple track MSR: ISO 7810, 7811, 7813; smart
card reader: EMVCo-approved

CONTACTLESS

ISO 14443 Types A and B, ISO 18092-
capable, EMVCo L1 certification, MIFARE,
supports major NFC/CTLS schemes

PERIPHERAL PORTS

Single connector supports RS-232, USB device,
USB host, Ethernet

AUDIO

Speaker

POWER SUPPLY

5-12 V DC, 4.8-5.2 W power consumption,
power over USB 5 V 500 mA

ENVIRONMENTAL

Operating temperature: 0° to 50° C (32° to 122°
F); storage temperature: -20° to 60° C (-4° to
140° F); relative humidity: 5% to 90%, non-
condensing

SECURITY

PCI PTS 5.X-approved

PHYSICAL

167 mm L × 80 mm W × 44 mm H, 310 g

OTHER STANDARD FEATURES

2 SAM slots, backlit keypad, uSD memory slot

OPTIONS/ACCESSORIES

Privacy shield, mounting adapter, power over
Ethernet (POE 802.3af), cables backward
compatible with VX

P400 PLUS

Memory: 1024 MB (512 MB Flash, 512 MB
SDRAM)
Connectivity: 5 GHz + 2.4 GHz WiFi, Bluetooth
4.2 BLE